



Extrema® corner protector



The Extrema® corner protector

The Extrema® corner protector is made from 100% Dyneema® and has the highest abrasion resistance of any fiber. Because of the two Velcro straps the corner protector is extremely easy to mount on the sling. The flexible Dyneema® pad makes it possible to use the sling in any situation without a fixed angle.

The corner protector is perfect for repetitive loadouts of payloads with extremely sharp edges. The lifetime of a round sling will be significantly longer and much safer with Extrema® corner protections on the bearing points, angles and sharp edges. You will also comply with the EN Standard 1492-2 for round slings.

The main application for Extrema® protection products is the protection of lifting equipment and the object that will be lifted. It can be mounted on synthetic round slings, webbing slings, steel wire rope and chains, lashings and synthetic ropes.

Features

- ✓ Highest abrasion resistance of any fiber
- ✓ Excellent dynamic toughness
- ✓ Very low elongation
- ✓ Excellent flex fatigue resistance
- ✓ Superior cut resistance
- ✓ Exceptional flexibility
- ✓ Superior tear resistance
- ✓ Significantly longer lifespan of round slings and webbing slings
- ✓ It always stays in the right place: easy to place on the anchoring points, or the most vulnerable places.

Contact

Would you like to know more about our Extrema® corner protector? Please contact our sales department.

Tel.: +31 (0) 594 2000 10

E-mail: sales@lift-tex.nl

<http://www.extreemasoftslings.com/>

Type	Suitable for Round sling load capacity	Suitable for Lifting sling webbing width	Dimensions		
			Width	Length	Thickness
EXCP/85/500*	1T-6T	up to 75mm	85mm	500mm	12mm
EXCP/115/500*	8T	up to 100mm	115mm	500mm	12mm
EXCP/135/500*	10T-12T	up to 120mm	135mm	500mm	12mm
EXCP/160/500*	15T	up to 150mm	160mm	500mm	12mm
EXCP/190/600	20T-25T	up to 180mm	190mm	600mm	12mm
EXCP/230/800	30T-40T	up to 200mm	230mm	800mm	12mm
EXCP/260/800	45T	up to 240mm	260mm	800mm	12mm
EXCP/290/800	50T-55T	up to 240mm	290mm	800mm	12mm

* minimum order quantity is 2